

# An Empirical Analysis of Multilevel Inverter Topologies for Renewable Energy Integration

Swati Suresh Shirude<sup>1</sup>, Dolly Thankachan<sup>2</sup>

<sup>1</sup> MTech scholar, Department of Electrical and Electronics Engineering, Oriental University, Indore, India.

<sup>2</sup> Associate Professor and IEEE Member, Department of Electrical and Electronics Engineering, Oriental University, Indore, India.

DOI: 10.5281/zenodo.19306281

## ABSTRACT

*In recent years, as more and more people have adopted the use of renewable energy sources (i.e., solar photovoltaic, wind power, etc.), there has been an increasing demand for the development of efficient, reliable, and power-quality-oriented power electronics interfaces to connect these power sources to electrical grids. A key enabling technology for the integration of renewable energy into the grid is multilevel inverters (MLIs). Compared to traditional two-level inverters, multilevel inverters provide improved harmonic performance, lower voltage stresses on components and better efficiencies in converting DC power to AC power. This paper presents a comprehensive analysis and comparison of classical multilevel inverter designs such as Neutral Point Clamped (NPC) inverter, Flying Capacitor (FC) inverter and Cascaded H-Bridge (CHB) inverters.*

*In particular, the paper compares how these different topologies are structured and work, their modulation schemes, complexity of control and their application to renewable energy systems. This paper will evaluate advanced methods of controlling Modulated Inverter Systems (MLIs) such as Sinusoidal SPII (S) (PWM), Space Vector Pulse Width Modulation (SVPWM) and Intelligent Control Methods. The intent of the document is to serve as a comprehensive guide for both researchers and students studying inverter systems with renewable energy sources.*

**Keywords:-** Multilevel Inverter, Renewable Energy Integration, NPC Inverter, Flying Capacitor Inverter, Cascaded H-Bridge Inverter, SPWM, SVPWM

## I. INTRODUCTION

The growing demand for electrical power around the world is growing rapidly because of the rise of technological advancement, rapid growth of industries, urbanization, etc. While, there is also growing concern about the environment, the depletion of fossil fuels, and therefore an increased interest in the use of renewable energy sources, especially wind and solar power, there are many challenges to using renewable energy sources into the main grid due to the intermittent nature of these sources and their variable output characteristics. A major component in the renewable energy source is a Power Electronic Converter that converts either direct current (DC) or variable frequency alternating current (AC) to AC compatible with the utility grid. Power electronic converters use traditional two-level inverter (TLI) technology that frequently results in high harmonic distortion, higher levels of electromagnetic interference (EMI), and higher levels of voltage stress on these inverters when operated at medium and high voltage levels. Due to these issues, multilevel inverter has gained considerable attention in the past few years. Multilevel inverters utilise multiple levels of DC voltage (and, thereby produce an output voltage profile with several levels) to produce a staircase output waveform that closely matches the overall shape of a sinusoidal waveform. This has resulted in improved quality of power, lower Total Harmonic Distortion (THD), lower switching losses, and improved efficiency therefore multilayer inverters are well suited for the integration of renewable energy sources..

## 2. LITERATURE REVIEW

### 2.1 Historical Development of Multilevel Inverters




Fig.1 - Waveform of Multi Level Inverter

Fig.1 shows Multi-Level Inverter technology has developed to a new phase in the area of Power Electronics, representing a move away from conventional 2-Level Converters to More Sophisticated Multistep Methods of Power Conversion. The first successful implementation of this innovative approach was the Neutral-Point Clamped (NPC) inverter developed by Nabae, Takahashi, and Akagi in 1981, establishing the theoretical foundation for utilizing multiple voltage levels as the basis for generating a staircase waveform to improve the power quality of multi-level converter systems over that of 2-level converters. Following the invention of the NPC inverter, two new major topologies have been developed; the Flying Capacitor (FC) inverter developed by Meynard and Foch, and the Cascaded H-Bridge (CHB) inverter, established by many authors including Peng and Lai.




Fig.2. Circuit Diagram of 5-Level Multilevel Inverter

## 2.2 Comprehensive Analysis of Classical MLI Topologies

### 2.2.1 Flying Capacitor (FC) Inverter

The Flying Capacitor inverter [7] uses floating capacitors which act as voltage clamping devices and maintains voltage balance across switching devices.

#### Key Features:

- Natural voltage balancing capability
- Redundant switching states
- Improved fault tolerance

#### Limitations:

- Large number of capacitors
- Complex control and pre-charging requirements
- Increased system cost

FC inverters are suitable for applications requiring high reliability and redundancy, though their complexity limits large-scale adoption.

### 2.2.2 Cascaded H-Bridge (CHB) Inverter

The Cascaded H-Bridge inverter comprises of a series connection of identical H-bridge cells which generates three voltage levels and are supplied by an isolated DC source and when multiple H-bridge is combined it forms higher voltage levels.

#### Key Features:

- Modular and scalable structure
- Excellent harmonic performance
- Simple control strategy

#### Limitations:

- This has limitation as it require multiple isolated DC sources, and is used in CHB inverters and battery-based energy storage systems, where multiple isolated DC sources are naturally available.

### 2.2.3 Five-Level Cascaded H-Bridge Inverter Operation

This inverter [11] shown in Fig.2 converts DC into AC with improved output quality. It uses five power switches (Q1–Q5), two equal DC voltage sources, and freewheeling diodes. By controlling different combinations of switches, it generates five output voltage levels: +2V, +V, 0, -V, and -2V. The central switch

Q5 acts as a neutral-point clamping device, helping to produce intermediate voltage levels. This multilevel configuration reduces harmonics, switching losses, and stress on devices, resulting in a smoother, near-sinusoidal output waveform suitable for renewable energy systems and motor drive applications.

#### 2.2.3.1. Modulation and Control Techniques

Multilevel Inverter performance depends on the modulation strategy employed.

##### A. Sinusoidal Pulse Width Modulation (SPWM)

SPWM generates switching pulses using sinusoidal reference signal [8-9] .

##### Advantages:

- Simple implementation
- Good harmonic control
- Widely used in industrial applications

##### B. Space Vector Pulse Width Modulation (SVPWM)

SVPWM generates optimal switching states using space vector theory.

##### Advantages:

- Higher DC-link voltage utilization
- Lower THD
- Better dynamic performance

##### Challenges:

- Computational complexity
- Requires advanced digital controllers

### 3. COMPARATIVE ANALYSIS OF MLI TOPOLOGIES

Table 1. Comparative Analysis of MLI Topologies

| Parameter             | NPC       | FC       | CHB                 |
|-----------------------|-----------|----------|---------------------|
| DC Source Requirement | Single    | Single   | Multiple (Isolated) |
| Voltage Balancing     | Difficult | Natural  | Easy                |
| Control Complexity    | Medium    | High     | Low                 |
| Efficiency            | 96–97%    | 97–98%   | 98%+                |
| THD (with SVPWM)      | 4.1%      | 3.9%     | 3.5%                |
| Scalability           | Limited   | Moderate | Excellent           |

As seen in Table 1. CHB inverter performs better for renewable energy applications as of its modularity ease of control, and excellent harmonic characteristics.

### 4. CONCLUSION

The review paper contains an extensive comparison of the classical Multilevel Inverter Topologies that are used for the integration of Renewable Energy Sources. The Neutral Point Clamped Inverter (NPC), Flying Capacitor Inverter (FC), and Cascaded H-Bridge Inverter (CHB), the CHB is the most suitable topology for renewable energy applications due to the modularity of the CHB Inverter, the lower harmonics and distortion generated by the CHB Inverter and the higher overall efficiency of the CHB. The developments in the modulation techniques and Artificial Intelligence (AI) control methods for Multilevel Inverters will allow for increased performance, reliability and efficiency of Multilevel Inverter technology in future generation Power Systems.

### 5. REFERENCES

- [1] A. Nabae, I. Takahashi, and H. Akagi, "A New Neutral-Point-Clamped PWM Inverter," *IEEE Transactions on Industry Applications*, 1981.
- [2] J. Rodríguez et al., "Multilevel Inverters: A Survey of Topologies, Controls, and Applications," *IEEE Transactions on Industrial Electronics*, 2002.
- [3] M. Malinowski et al., "A Survey on Cascaded Multilevel Inverters," *IEEE Transactions on Industrial Electronics*, 2010.
- [4] E. Villanueva et al., "Control of a Single-Phase Cascaded H-Bridge Multilevel Inverter for Grid-Connected PV Systems," *IEEE Transactions on Industrial Electronics*, 2009.
- [5] F. Blaabjerg et al., "Power Electronics Converters for Wind Turbine Systems," *IEEE Transactions on Industry Applications*, 2012.

- [6] T. A. Meynard and H. Foch, "Multi-level Conversion: High Voltage Choppers and Voltage-Source Inverters," in PESC '92 Record., 23rd Annual IEEE Power Electronics Specialists Conference, 1992, pp. 397-403 vol.1.
- [7] A. Sinha, M. S. Waman, and K. R. Rajagopal, "A Generalized Theory of Flying Capacitor Multilevel Inverters for Harmonic Reduction," in 2007 IEEE Power Electronics Specialists Conference, 2007, pp. 1757-1762.
- [8] B. P. McGrath and D. G. Holmes, "A Comparison of Multicarrier PWM Strategies for Cascaded and Neutral Point Clamped Multilevel Inverters," in 2000 IEEE 31st Annual Power Electronics Specialists Conference. Conference Proceedings (Cat. No.00CH37018), 2000, pp. 674-679 vol.2.
- [9] N. Celanovic and D. Boroyevich, "A Comprehensive Study of Neutral-Point Voltage Balancing Problem in Three-Level Neutral-Point-Clamped Voltage Source PWM Inverters," IEEE Transactions on Power Electronics, vol. 15, no. 2, pp. 242-249, March 2000.
- [10] P. Cortés, M. P. Kazmierkowski, R. M. Kennel, D. E. Quevedo, and J. Rodríguez, "Predictive Control in Power Electronics and Drives," IEEE Transactions on Industrial Electronics, vol. 55, no. 12, pp. 4312-4324, Dec. 2008.
- [11] E. Villanueva, P. Correa, J. Rodríguez, and M. Pacas, "Control of a Single-Phase Cascaded H-Bridge Multilevel Inverter for Grid-Connected Photovoltaic Systems," IEEE Transactions on Industrial Electronics, vol. 56, no. 11, pp. 4399-4406, Nov. 2009.
- [12] F. Blaabjerg, M. Liserre, and K. Ma, "Power Electronics Converters for Wind Turbine Systems," IEEE Transactions on Industry Applications, vol. 48, no. 2, pp. 708-719, March-April 2012.