

Automatic Auditorium Power and Fire Safety System

Prof. S. D. Lavange¹, Miss. Tejal Patil², Miss. Vaishnavi Barhate³, Miss. Anisha Talole⁴, Miss. Tejal Girhe⁵, Miss. Sakshi Ingle⁶

¹Professor, Department of Electrical Engg, Dr. V. B. Kolte College of Engineering, Malkapur, India

^{2,3,4,5,6,7}Students, Department of Electrical Engg, Dr. V. B. Kolte College of Engineering, Malkapur, India

DOI: 10.5281/zenodo.19307117

ABSTRACT

This project presents the design and implementation of an Automated Auditorium Power Control and Fire Detection System aimed at enhancing safety, energy efficiency, and operational convenience in public spaces. The system integrates automatic lighting and electrical load management with real-time fire detection and alarm mechanisms. Power consumption in the auditorium is optimized through sensors and programmable controllers, ensuring lights, fans, and other devices operate only when needed. Simultaneously, smoke and fire sensors continuously monitor the environment and trigger alarms, notifications, and emergency protocols in the event of a fire, thereby safeguarding occupants and property. The system is controlled using a microcontroller-based platform, enabling seamless automation and integration with existing electrical infrastructure. This approach not only reduces energy wastage but also provides a reliable and proactive solution for fire safety management in auditoriums and similar public venues. Experimental results demonstrate improved energy efficiency and rapid fire detection, validating the effectiveness of the proposed system.

Keywords: - Auditorium Automation, Power Control System, Energy Efficiency, Fire Detection etc.

1. INTRODUCTION

Auditoriums are integral components of educational institutions, theaters, conference halls, and other public venues. They host various events such as lectures, seminars, cultural programs, and performances, often accommodating a large number of people simultaneously. Efficient management of an auditorium requires attention not only to lighting, ventilation, and electrical appliances but also to safety measures, particularly fire detection and prevention. Traditionally, auditorium systems rely heavily on manual operation, where lights, fans, and other electrical devices are switched on or off by personnel. This manual operation can lead to several challenges, including energy wastage, inconsistent operation, and increased electricity costs, especially in large auditoriums with complex lighting and electrical arrangements. In addition to energy management, fire safety is a significant concern in auditoriums. Large gatherings increase the risk to human life in the event of a fire. Conventional fire detection systems may be limited in their responsiveness, relying on basic smoke detectors or human observation, which can delay the initiation of emergency protocols. Prompt detection and timely alerting are crucial for preventing casualties and minimizing property damage. Therefore, a system that integrates both automated power control and fire detection is necessary to improve efficiency, safety, and reliability. The Auditorium Power Control and Fire Detection System is designed to address these challenges by using a microcontroller-based automation system that combines energy management with real-time fire monitoring. The system employs sensors to detect occupancy in the auditorium, automatically switching on lights, fans, and other electrical equipment only when required. This automation significantly reduces unnecessary power consumption, ensures optimal use of electrical resources, and minimizes operational errors caused by human oversight. Scheduled control of devices further enhances energy efficiency, especially during events with variable usage patterns. Simultaneously, the system incorporates fire and smoke sensors strategically placed to detect signs of fire at an early stage. When a fire is detected, the system immediately triggers alarms, notifies authorities, and initiates safety protocols, such as activating fire suppression systems if available or guiding occupants to safety.

OBJECTIVE

- Utilize solar energy as the primary power source to reduce dependency on conventional electricity and promote renewable energy use.
- Implement accelerometer-based control to enable intuitive and gesture-driven robot movement.
- Develop a wireless communication interface between the accelerometer module (controller) and the robot for real-time motion control.
- Ensure efficient power management to maximize the performance and battery life of the solar-powered


system.

2. LITERATURE SURVEY

- **Izang et al. (2018)** Designed An SMS Based Fire Alarm and Detection System. The system works when fire or gas is detected by the sensors, the Arduino will trigger the GSM module to send SMS, sound the alarm system and trigger the servo motor. The disadvantage of this system is that the servo motor works at an angle of 170 degrees and hence cannot reduce fire outbreak as compared to using a pump motor.
- **Jinan (2018)** Designed and Implemented a Factory Security System that consist of a smoke sensor, a GSM (Global System for Mobile communication) module and a sound module. When the gas leakage is detected, an SMS will be sent to a number. The disadvantage of the system is that there is no device that can stop the gas leakage and hence, when there is fire outbreak the necessary device to extinguish the fire is not included in the system which may cost loss of properties.
- **E.Shilpa et al. (2017)** He has done a "Implementation of Automatic Room Light Controller with Visitor Counter Design using 8051 Microcontroller"[4]. This project compacts with the usage of the energy in this competitive world of electricity. This project is well-organized enough to let someone know about the accuracy of the person entered and have taken the exit from the room.
- **Subhankar Chatteraj et al. (2016)** has done a "Bidirectional Visitor Counter with Automatic Room Light Controller and Arduino as the master controller". This paper gives the basic idea of how to control the bidirectional visitor counter and room light counter using Arduino Mega and Ardiono(IDE). The cost of this technology is very economical.
- **Sonali K. Pawar et al. (2016)** has done a "Automatic Room Light Controller Using Microcontroller And Visitor Counter". This digital world Technology is very advanced and we prefer things to be done automatically without any human efforts. This project also helps to reduce human efforts. Also it is very useful to conserve resources.
- **Jinan (2018)** Designed and Implemented a Factory Security System that consist of a smoke sensor, a GSM (Global System for Mobile communication) module and a sound module. When the gas leakage is detected, an SMS will be sent to a number. The disadvantage of the system is that there is no device that can stop the gas leakage and hence, when there is fire outbreak the necessary device to extinguish the fire is not included in the system which may cost loss of properties.
- **Poonam et al. (2014)** Designed an Intelligent Fire Extinguisher System. the features are intelligent fire detection and suppression, locate the position of fire origin, effective power control of electricity, reporting through an SMS or email and effective usage of water supply, among the sensors used is a gas sensor which detect any type of smoke, this can send a false alarm and hence not reliable

3. WORKING & IMPLEMENTATION

The effectiveness and quick response in emergency management are crucial to reducing casualties. Real-time analysis of environmental conditions using IoT sensors which monitor temperature, humidity, pressure, and gases like CO and CO₂ can help detect or prevent disasters such as forest fires.



The proposed system continuously monitors these parameters and uploads data to the IoT cloud. When sensor readings exceed preset thresholds, it automatically sends an alert email to the user. Unlike existing systems that rely on robots for firefighting, this approach focuses on early detection and monitoring. Additionally, the system ensures secure communication between IoT devices, web services, and mobile platforms using data encryption, secure authentication, and block cipher algorithms for safe data transmission. Each IoT device in the auditoriums fire detection system communicates wirelessly via 4G with a central web service that stores and processes data. These devices are Arduino-based and equipped with sensors to measure temperature, humidity, atmospheric pressure, and pollutant gases like CO and CO₂ (for air quality monitoring). The system also provides Automatically manage and optimize electrical loads (lights, HVAC, AV equipment) to save energy,

Detect fire early (smoke/heat/flame) and trigger automated safety actions (alarms, evacuation lights, power isolation), Provide manual override and remote monitoring/control, Log events for maintenance and safety audits.

Working of system

The Auditorium Power Control and Fire Detection System operate by integrating automated electrical load management with continuous fire monitoring using a microcontroller-based control unit. The system is designed to ensure energy efficiency while maintaining a high level of safety within the auditorium environment. When the system is powered ON, sensors placed at strategic locations monitor the presence of occupants inside the auditorium. Based on the input from these sensors, the microcontroller automatically controls electrical devices such as lights, fans, and other appliances. If occupancy is detected, the required electrical loads are switched ON, and when the auditorium is vacant, the system automatically turns them OFF. This automation helps in reducing unnecessary power consumption and eliminates manual errors. Simultaneously, the fire detection module continuously monitors environmental conditions using smoke and temperature sensors. Under normal conditions, these sensors send regular status signals to the microcontroller. If smoke or a sudden rise in temperature is detected, indicating a possible fire, the system immediately activates an alarm system. The alarm alerts occupants and authorities, allowing quick evacuation and emergency response. In advanced configurations, the system can also disconnect the main power supply to prevent further fire hazards and can be linked to communication modules for sending alert messages. The integrated working of power control and fire detection ensures safe, efficient, and reliable operation of the auditorium, making the system suitable for modern public spaces.

4. CONCLUSION

The Auditorium Power Control and Fire Detection System successfully demonstrates the integration of automation, energy management, and safety in a single intelligent platform. By automating the control of electrical appliances such as lighting and ventilation based on occupancy, the system effectively reduces energy wastage and operational costs. At the same time, the inclusion of real-time fire and smoke detection enhances safety by providing immediate alerts and enabling quick emergency response. The use of a microcontroller-based architecture ensures reliable operation, flexibility, and ease of implementation in auditoriums of different sizes. The system minimizes human intervention, reduces the chances of error, and ensures continuous monitoring of both power usage and fire hazards. Overall, this project offers a cost-effective, efficient, and scalable solution for modern auditoriums, contributing to improved safety, energy efficiency, and sustainable infrastructure management.

5. REFERENCES

- [1] Sharma, Abhinav Kumar, M d Faiz Raza Ansari, M d Firoz Siddiqui, and Mirza AtaullahBaig. Iot Enabled Forest Fire Detection And Online Monitoring System ."
- [2] Owayjan, Freiha, Achkar, Abdo &M allah, (2014, April),,Firoxio: Forest fire detection and alerting system" In Mediterranean Electro technical Conference(M ELECON), 2014 17th IEEE (pp . 177- 181). IEEE.
- [3] G. Hristov, J. Raychev, D. Kinaneva, and P. Zahariev, Emerging Methods for Early Detection of Forest Fires Using Unmanned Aerial Vehicles and Lorawan Sensor Networks, 2018 28th EAEEIE Annual Conference (EAEEIE), 2018
- [4] G. B. Neumann, V. P. D. Almeida, and M. Endler, Smart Forests: fire detection service, 2018 IEEE Symposium on Computers and Communications (ISCC), 2018.
- [5] Eunna Jang, Yoojin Kang, Jungho Im, Dong-Won Lee, Jongmin Yoon, and Sang-Kyun Kim, "Detection and monitoring of forest fires using himawari-8 geostationary satellite data in south korea," Remote Sensing, vol. 11, no. 3, 2019.
- [6] Rob Bailey and Jaclyn Yeo, The Burning Issue: Managing Wildfire Risk, Marsh & McLennan Insights, 2019.
- [7] Shamsoshoara, F. Afghah, A. Razi, S. Mousavi, J. Ashdown, and K. Turk, "An autonomous spectrum management scheme for unmanned aerial vehicle networks in disaster relief operations," 2019
- [8] Adekunle A., Umanah I.I., Ibe K.E. and Imonikosaye M.R. (2018) Statistical analysis of fire outbreaks in homes and public buildings in Nigeria. A Case Study of Lagos State, (pp. 21 - 30). 2. Amy, T., et al. (2019)
- [9] Study on water-based fire extinguishing agent formulations and properties. International Symposium on Safety Science and Technology, (pp. 650 - 654) 6. Shehab, J. N. (2018)
- [10] Design and Implementation of Factory Security System. (PP. 162 - 171) 7. Qin, W. Jiashuo, C. and Chuang, Z. (2018)
- [11] Intelligent Smoke Alarm System with Wireless SensorNetwork Using ZigBee, (pp. 1 - 10) 8.
- [12] Aydin, B., Selvi, E., Tao, J. and Starek, M. J. (2019) Use of Fire-Extinguishing Balls for a Conceptual System of Drone-Assisted Wildfire Fighting, (PP.1 - 15) 9.