

Optimization of Laser Beam Machining Parameters Using AI Techniques: A Comprehensive Literature Review

Nitin A. Kharche¹, Vishal N. Sulakhe², Kiran Kaware³, Prasad Baviskar⁴

¹Research Scholar, Department of Mechanical Engineering, Sandip University, Nasik

²Associate Professor, Department of Mechanical Engineering, Sandip University, Nasik

³Assistant Professor, Department of Mechanical Engineering, Sandip University, Nasik

⁴Professor, Department of Mechanical Engineering, Late Sau. Kantabai Bhavarlalji Jain College of Engineering, Chandwad, Nashik

DOI: 10.5281/zenodo.19333629

ABSTRACT

Laser beam machining (LBM) has emerged as a critical non-conventional manufacturing technology for precision machining of advanced materials across aerospace, automotive, biomedical, and electronics industries. The optimization of laser machining parameters is essential for achieving superior surface quality, dimensional accuracy, and process efficiency. Traditional optimization methods, including trial-and-error approaches and classical statistical techniques, often prove inadequate for capturing the complex, nonlinear relationships between process parameters and machining outcomes. This comprehensive review examines the application of artificial intelligence (AI) techniques for optimizing laser beam machining parameters, covering artificial neural networks (ANNs), adaptive neuro-fuzzy inference systems (ANFIS), support vector machines (SVM), deep learning architectures, and metaheuristic optimization algorithms including genetic algorithms (GA) and particle swarm optimization (PSO). The review synthesizes findings from recent studies demonstrating that hybrid AI approaches, particularly ANFIS-PSO and ANN-GA combinations, achieve prediction accuracies exceeding 95% with R^2 values reaching 0.98. Key performance metrics including surface roughness, kerf width, heat-affected zone (HAZ), and material removal rate (MRR) are analyzed across various materials including metals, ceramics, composites, and polymers. The review identifies that AI-optimized parameters can improve machining efficiency by 15-30% compared to conventional optimization methods while significantly reducing experimental costs and time. Current challenges including data availability, model interpretability, and real-time implementation are discussed alongside future research directions emphasizing explainable AI, transfer learning, and integration with Industry 4.0 frameworks.

Keywords:- Laser beam machining, artificial intelligence, parameter optimization, machine learning, neural networks, metaheuristic algorithms, surface roughness, material removal rate

1. INTRODUCTION

1.1 Background on Laser Beam Machining

Laser beam machining represents one of the most versatile and precise non-conventional manufacturing processes, enabling high-quality processing of materials that are difficult or impossible to machine using traditional methods. Technology has evolved significantly since its inception, with modern systems offering unprecedented control over material removal mechanisms through precise energy delivery [1]. Contemporary laser machining encompasses various techniques including laser cutting, drilling, ablation, surface texturing, and hybrid processes, each requiring careful optimization of multiple interdependent parameters. The fundamental advantage of laser machine lies in its contactless nature, which eliminates tool wear, mechanical stresses, and vibrations while enabling micro-scale precision and minimal thermal damage [2].

The complexity of laser-material interactions involves highly nonlinear physical phenomena including absorption, heat conduction, melting, vaporization, and plasma formation. These interactions are acutely sensitive to laser parameters such as power, wavelength, pulse duration, repetition rate, scanning speed, and focal position [3]. Additionally, material-specific properties including thermal conductivity, absorption coefficient, melting temperature, and microstructural characteristics significantly influence machining outcomes. This multifaceted nature creates a vast parameter space where traditional optimization approaches struggle to identify optimal combinations efficiently. Machine learning for multi-dimensional optimization has demonstrated the capability to address these challenges by capturing complex inter-relationships that conventional physical models cannot adequately represent [4].

1.2 Need for Parameter Optimization

The quality and efficiency of laser beam machining are critically dependent on the selection of appropriate process parameters. Improper parameter settings can lead to excessive heat-affected zones, poor surface finish, dimensional inaccuracies, thermal distortion, and material waste. For instance, in laser cutting of composite materials, the selection of laser power and cutting speed directly influences surface roughness and kerf width, with complex nonlinear interactions that vary across different material thicknesses [5]. Similarly, in laser ablation processes, the combination of pulse energy, scanning speed, and number of scans determines ablation depth, width, and the extent of thermal damage.

Traditional parameter optimization approaches, including one-factor-at-a-time experiments and full factorial designs, are time-consuming, resource-intensive, and often fail to capture interaction effects between multiple parameters. Response Surface Methodology (RSM), while widely used, relies on polynomial regression models that may inadequately represent highly nonlinear behaviors characteristic of laser machining processes [1]. The need for more sophisticated optimization methodologies has become increasingly apparent as industries demand higher precision, reduced production costs, and faster process development cycles. AI-based optimization techniques offer a paradigm shift by enabling data-driven modeling, prediction, and optimization without requiring complete understanding of underlying physical mechanisms.

1.3 Role of AI in Manufacturing

Artificial intelligence has revolutionized manufacturing optimization by providing powerful tools for pattern recognition, predictive modeling, and intelligent decision-making. In the context of laser beam machining, AI techniques excel at learning complex mappings between input parameters and output responses from experimental or simulation data [6]. Machine learning algorithms can identify optimal parameter combinations that maximize desired objectives while satisfying multiple constraints, a capability particularly valuable for multi-objective optimization scenarios common in laser machining. The integration of AI into laser systems enables real-time process monitoring, adaptive parameter adjustment, and predictive quality control, advancing toward fully autonomous manufacturing systems.

Deep learning architectures, particularly convolutional neural networks, have shown remarkable success in analyzing in-situ monitoring data from laser processes, enabling real-time prediction of machining quality [7]. Hybrid approaches combining neural networks with metaheuristic optimization algorithms have demonstrated superior performance compared to standalone methods, achieving prediction accuracies exceeding 98% in some applications [8]. Furthermore, AI-driven optimization significantly reduces the experimental burden by requiring fewer trials to identify optimal parameters, thereby decreasing development time and costs while improving process reliability.

1.4 Scope and Organization

This comprehensive literature review examines the state-of-the-art applications of artificial intelligence techniques for optimizing laser beam machining parameters. The review synthesizes recent research across diverse AI methodologies, materials, and laser processes to provide insights into current capabilities, best practices, and future directions. Section 2 discusses fundamental aspects of laser machining including process parameters and quality metrics. Section 3 examines various AI techniques including ANNs, ANFIS, SVM, and deep learning approaches. Section 4 explores methodology of methodology of optimization and hybrid methodologies. Section 5 analyzes the integration of AI with response surface methodology. Section 6 presents applications across different materials and processes. Section 7 provides performance analysis and validation studies. Section 8 discusses challenges and future research directions, followed by conclusions in Section 9.

2. LASER BEAM MACHINING: PROCESS PARAMETERS AND QUALITY METRICS

2.1 Types of Laser Machining Processes

Laser beam machining encompasses several distinct processes, each characterized by specific mechanisms of material removal and application domains. CO₂ laser cutting remains widely used for thick-section cutting of metals, polymers, and composites, operating at 10.6 μm wavelength with continuous or pulsed modes [9]. Fiber lasers have gained prominence due to superior beam quality, higher efficiency, and excellent cutting precision for thin materials, particularly for steel processing where parameters like laser power, cutting speed, and assist gas pressure critically influence surface roughness and dimensional accuracy [10]. Ultrafast laser machining, utilizing femtosecond and picosecond pulses, enables near-damage-free processing of hard and brittle materials through minimized heat-affected zones and precise material removal [1].

Laser-assisted machining combines laser heating with conventional cutting tools to enhance machinability of difficult-to-cut materials. Studies on laser-assisted turning of ceramics and superalloys have demonstrated that appropriate laser power preheating significantly reduces cutting forces and improves surface quality [11]. Laser powder bed fusion and laser-directed energy deposition represent additive manufacturing variants where laser

parameters determine track geometry, density, and mechanical properties. Each process type presents unique optimization challenges requiring tailored AI approaches that account for process-specific physical phenomena and quality requirements.

2.2 Critical Process Parameters

The primary laser process parameters include laser power (or energy), pulse duration, repetition rate, scanning/cutting speed, focal position, and beam geometry. Laser power directly determines the energy input to the material, affecting depth of penetration, material removal rate, and thermal damage extent. Research on femtosecond laser machining of single crystal diamond identified laser power, scanning speed, and number of scans as key parameters, with interaction effects significantly influencing machining performance [1]. Pulse duration differentiates between continuous wave, nanosecond, picosecond, and femtosecond lasers, with shorter pulses generally producing reduced heat-affected zones but requiring higher peak powers.

Scanning speed affects the interaction time between laser and material, with faster speeds reducing heat accumulation but potentially decreasing material removal depth. Studies on CO₂ laser cutting of FFF-printed composites found that cutting speed is the most dominant factor affecting kerf width, showing inverse relationships where increased speed decreased kerf dimensions [5]. Focal position relative to the workpiece surface critically influences beam diameter and power density at the interaction zone. Investigation of fiber laser cutting of steel sheets demonstrated that focal point position significantly affects both surface roughness and kerf width, with positive focal positions decreasing roughness while increasing kerf width [12]. Secondary parameters including assist gas type and pressure, material thickness, and environmental conditions further complicate the optimization landscape.

2.3 Quality Metrics and Response Variables

Laser machining quality is assessed through multiple response variables that often present conflicting optimization objectives. Surface roughness (Ra, Rz, Sa) quantifies the textural quality of machined surfaces, with lower values indicating smoother finishes desirable for most applications. Studies on laser-assisted machining of SiC ceramics achieved minimum surface roughness of 0.418 μm through optimized parameter combinations using AI-based prediction models [13]. Kerf width and taper angle characterize dimensional accuracy in cutting processes, with tighter tolerances required for precision applications. Research on CO₂ laser cutting of PLA-CF composites identified minimum kerf width of 0.809 mm at optimized parameters, demonstrating the critical importance of parameter selection [5].

Heat-affected zone width indicates thermal damage extent, particularly critical for materials sensitive to thermal alterations or when maintaining microstructural integrity is essential. Investigations of laser processing parameters for composites emphasized minimizing HAZ to prevent thermal degradation of matrix materials and fiber-matrix interfaces [14]. Material removal rate quantifies process efficiency, representing the volume of material removed per unit time. Optimization studies on femtosecond laser machining of SiC achieved significant improvements in both machining efficiency and quality through AI-based parameter optimization [2]. Additional quality metrics include dimensional accuracy, edge quality, microstructural changes, residual stresses, and defect formation (recast layer, dross, spatter, cracks, delamination).

Table 1: Key Process Parameters and Quality Metrics in Laser Beam Machining

Category	Parameters/Metrics	Typical Range	Impact on Quality	References
Laser Parameters	Power/Energy	10-5000 W	MRR, HAZ, depth	[1] [10]
	Pulse Duration	fs to CW	HAZ, precision	[3] [2]
	Scanning Speed	1-3000 mm/min	Surface quality, kerf	[5] [12]
	Repetition Rate	1-500 kHz	Heat accumulation	[2]
	Focal Position	-5 to +5 mm	Energy density	[12]
Quality Metrics	Surface Roughness (Ra)	0.4-15 μm	Functional performance	[13] [11]
	Kerf Width	0.1-5 mm	Dimensional accuracy	[5] [9]
	Heat-Affected Zone	2-200 μm	Material integrity	[14] [15]
	Material Removal Rate	0.1-50 mm ³ /min	Process efficiency	[2]
	Taper Angle	0.1-10°	Geometric precision	[9]

3. ARTIFICIAL INTELLIGENCE TECHNIQUES FOR PARAMETER OPTIMIZATION

3.1 Artificial Neural Networks (ANNs)

Artificial neural networks have emerged as the most widely adopted AI technique for laser machining parameter optimization due to their universal approximation capability and ability to model complex nonlinear relationships. ANNs consist of interconnected nodes organized in layers that learn input-output mappings through iterative training on experimental data. Research on laser powder bed fusion process optimization employed ANN models with 7 neurons in the hidden layer to predict multiple part properties including surface

roughness, relative density, microhardness, and dimensional accuracy, achieving R^2 scores of 0.59 through k-fold cross-validation [16]. The architecture selection, typically involving feedforward backpropagation networks with 1-3 hidden layers, critically influences prediction performance.

Studies comparing ANN architectures for machining parameter prediction found that networks trained with Levenberg-Marquardt algorithms consistently outperformed gradient descent methods, achieving higher accuracy with fewer iterations [17]. Investigation of fiber laser cutting parameters for steel plates demonstrated that ANNs accurately predicted optimal cutting quality, with neural network-based optimization models showing superior performance compared to traditional approaches [10]. A significant advantage of ANNs is their ability to predict multiple responses simultaneously from the same input parameters, enabling multi-objective optimization. Research on laser-assisted machining utilized ANN models with 4-10-3 architecture to model relationships between surface roughness, cutting force, and temperature, achieving R-values of 0.98 [18]. However, ANNs face challenges including the need for substantial training data, susceptibility to overfitting, and limited interpretability of learned relationships. Small dataset applications have shown that careful architecture design and regularization techniques can achieve reliable predictions even with limited experimental trials. Studies employing Taguchi-based experimental designs successfully trained ANNs with as few as 27 data points, demonstrating prediction accuracies exceeding 90% for surface roughness in aluminum alloy machining [17]. The integration of ANNs with optimization algorithms represents a powerful approach for identifying optimal parameter combinations, as demonstrated in numerous laser machining applications.

3.2 Adaptive Neuro-Fuzzy Inference Systems (ANFIS)

Adaptive Neuro-Fuzzy Inference Systems combine the learning capabilities of neural networks with the interpretability of fuzzy logic, making them particularly suitable for laser machining optimization where expert knowledge and data-driven learning can be synergistically integrated. ANFIS architectures utilize fuzzy if-then rules with membership functions adapted through neural network training algorithms, providing both prediction capability and insight into parameter relationships. Research on CO₂ laser cutting of 3D-printed PLA-CF composites demonstrated that particle swarm optimization-based ANFIS achieved superior accuracy compared to multiple linear regression and ant colony optimization-based ANFIS, with the lowest mean squared error and highest correlation coefficient for predicting surface roughness and kerf width [5].

Comparative studies between ANFIS and other AI techniques have consistently shown ANFIS advantages in capturing nonlinear behaviors with relatively small datasets. Investigation of laser-assisted turning of Nitinol shape memory alloys found that ANFIS exhibited superior performance compared to RSM and ANN for predicting cutting force and surface roughness, with better agreement with empirical findings [19]. The fuzzy inference mechanism enables ANFIS to handle uncertainties inherent in laser machining processes, such as material property variations and environmental fluctuations. Studies applying ANFIS to laser processing parameter optimization reported that the technique effectively modeled complex interactions between laser power, cutting speed, and material properties, achieving prediction accuracies comparable to or exceeding deep learning approaches while requiring significantly less computational resources.

The hybrid nature of ANFIS facilitates integration with optimization algorithms for parameter tuning and rule optimization. Research has shown that combining ANFIS with metaheuristic algorithms such as genetic algorithms, particle swarm optimization, and ant colony optimization significantly enhances prediction performance. ANFIS models optimized through these hybrid approaches have achieved mean absolute percentage errors below 3% in various laser machining applications, demonstrating robust predictive capability across diverse materials and process conditions [5]. The interpretability of ANFIS rules provides valuable insights into parameter influences, enabling engineers to understand and validate optimization recommendations.

3.3 Support Vector Machines/Regression (SVM/SVR)

Support Vector Machines and Support Vector Regression offer robust machine learning approaches for laser machining parameter optimization, particularly effective in high-dimensional spaces with limited training data. SVR employs kernel functions to map input data into higher-dimensional feature spaces where nonlinear relationships can be approximated through linear models, providing excellent generalization capabilities. Research on laser-assisted machining of SiC ceramics demonstrated that Support Vector Regression optimized with grey wolf optimization algorithm achieved coefficient of determination (R^2) of 0.98676 with average relative error less than 2.624% for surface roughness prediction [13]. The robustness of SVR against overfitting makes it particularly suitable for laser machining applications where experimental data may be sparse or noisy.

Kernel selection critically influences SVR performance, with radial basis function (RBF) kernels most commonly employed for laser machining optimization due to their ability to capture complex nonlinear patterns. Studies comparing different kernel types found that RBF kernels consistently outperformed linear and polynomial kernels for predicting laser cutting quality metrics. The regularization parameter and kernel parameters require careful tuning, typically accomplished through cross-validation or metaheuristic optimization

algorithms. Investigation of CO₂ laser cutting of thermoplastics employed multiple machine learning approaches including SVR, demonstrating that proper hyperparameter optimization is essential for achieving high prediction accuracy [20].

Advantages of SVR include strong theoretical foundations, convex optimization guaranteeing global optima, and effectiveness with small to medium-sized datasets. Research applications have shown SVR achieving competitive or superior performance compared to ANNs and ANFIS in several laser machining scenarios, particularly when training data is limited. However, SVR faces challenges in computational efficiency for very large datasets and requires careful preprocessing of input features. Recent studies have explored hybrid SVR approaches combined with feature selection algorithms and ensemble methods to enhance prediction performance, achieving notable improvements in accuracy and computational efficiency for laser parameter optimization tasks.

3.4 Deep Learning Approaches

Deep learning architectures, particularly convolutional neural networks (CNNs) and recurrent neural networks (RNNs), have recently gained attention for laser machining optimization, especially for applications involving in-situ monitoring and real-time quality prediction. CNNs excel at extracting hierarchical features from high-dimensional data such as images of laser-induced melt pools or machined surfaces. Research on laser-directed energy deposition developed an innovative feature fusion deep learning network combining dynamic image features and static processing parameters, achieving width prediction accuracy of 98.45% and demonstrating over 10% improvement compared to conventional deep learning models [7]. These advanced architectures enable extraction of complex patterns from monitoring data that would be difficult to capture using traditional feature engineering approaches.

Deep encoder-decoder convolutional neural networks have been applied to predict thermal fields in additive manufacturing processes, achieving sub-second computational times that are over 41,000 times faster than physics-based simulations while maintaining high accuracy [21]. This dramatic speed improvement enables real-time process simulation and control, opening pathways toward adaptive laser machining systems. The application of deep learning to laser ablation simulation demonstrated that neural networks trained on single-shot experimental datasets could successfully predict three-dimensional structures resulting from multiple laser pulses at arbitrary positions and energies, effectively addressing physics with irreversibility that conventional methods cannot handle [3].

Transfer learning approaches enable deep learning models trained on one laser machining application to be adapted to different materials or processes with minimal additional training data, addressing the data scarcity challenge common in advanced manufacturing. However, deep learning faces challenges including substantial data requirements, computational intensity, and limited interpretability compared to simpler AI techniques. Recent research emphasizes explainable AI methods such as Gradient Class Activation Mapping to visualize and interpret deep learning model decisions, improving trust and enabling process insights. Integration of deep learning with physics-based models represents a promising direction, combining data-driven learning with domain knowledge to achieve both accuracy and physical consistency in laser machining optimization.

Table 2: Comparison of AI Techniques for Laser Beam Machining Optimization

AI Technique	Advantages	Limitations	Typical Accuracy (R ²)	Data Requirements	Computational Cost
Key Applications	ANN	Universal approximation, multi-output capability	Black box, overfitting risk	0.90-0.96	Medium (50-500)
Medium	General parameter optimization [10], [16]	ANFIS	Interpretable rules, handles uncertainty	Rule explosion for many inputs	0.92-0.98
Small-Medium (30-300)	Medium	Complex nonlinear systems [5], [19]	SVR	Strong generalization, robust to noise	Kernel selection critical
0.94-0.98	Small-Medium (20-200)	Low-Medium	Limited data scenarios [13]	XGBoost/RF	High accuracy, feature importance
Less interpretable	0.95-0.99	Medium-Large (100-1000)	Medium-High	Multi-output prediction [20]	Deep Learning

AI Technique	Advantages	Limitations	Typical Accuracy (R ²)	Data Requirements	Computational Cost
Automatic feature learning, real-time capable	Data hungry, black box	0.93-0.98	Large (500+)	High	In-situ monitoring, image-based [3], [7]




Figure 1: Prediction accuracy comparison of different AI methods based on literature survey. The chart illustrates R² scores and mean squared error (MSE) values across various AI techniques, with XGBoost and ANFIS demonstrating superior performance.

4. METAHEURISTIC OPTIMIZATION ALGORITHMS

4.1 Genetic Algorithms (GA)

Genetic Algorithms represent one of the most established metaheuristic optimization techniques for laser machining parameter optimization, inspired by biological evolution through natural selection. GAs operate on populations of candidate solutions, applying selection, crossover, and mutation operators to iteratively evolve toward optimal parameter combinations. Research on laser heating and ultrasonic vibration composite assisted cutting of tungsten carbide employed genetic algorithms to optimize machining parameters by setting material removal rate as the objective variable and surface roughness as a constraint, successfully improving processing efficiency while maintaining required quality [22]. The population-based search enables GAs to explore multiple regions of the parameter space simultaneously, reducing susceptibility to local optima compared to gradient-based methods.

Studies combining genetic algorithms with neural networks for laser machining optimization have demonstrated synergistic benefits. Investigation of laser ablation of stainless steel utilized GA optimization of extreme learning machine predictions, achieving prediction accuracies of 94.0% for depth, 99.0% for width, 93.2% for material removal rate, and 91.2% for surface roughness after optimization [23]. The multi-objective optimization capability of GAs enables simultaneous optimization of conflicting objectives such as maximizing material removal rate while minimizing surface roughness and heat-affected zone. Research on laser cutting of FFF plates employed genetic algorithms with neural network-derived objective functions to optimize mean kerf angle and surface roughness, successfully identifying Pareto-optimal parameter combinations [9].

Genetic algorithm performance depends critically on parameter settings including population size, crossover rate, mutation rate, and selection strategy. Studies have found that adaptive parameter adjustment schemes often outperform fixed parameters, allowing the algorithm to balance exploration and exploitation dynamically. Comparison of genetic algorithms with other metaheuristic techniques for laser machining optimization has shown competitive performance, with GAs typically requiring moderate computational resources while achieving reliable convergence. Recent developments include hybrid GAs incorporating local search mechanisms, constraint handling techniques, and parallel processing capabilities to enhance optimization efficiency for complex laser machining problems involving multiple objectives and constraints.

4.2 Particle Swarm Optimization (PSO)

Particle Swarm Optimization has gained significant popularity for laser machining parameter optimization due to its simplicity, fast convergence, and effectiveness in high-dimensional search spaces. PSO simulates social

behavior of bird flocking or fish schooling, where particles (candidate solutions) move through the search space influenced by their own best experience and the best experience of the swarm. Research on laser powder bed fusion milling optimization employed hybrid ANN-PSO, achieving optimal surface roughness of 0.137 μm compared to 0.155 μm for ANN-GA and experimental minimum of 0.133 μm , demonstrating the effectiveness of PSO for fine-tuning optimal parameters [8]. The algorithm's ability to efficiently explore the parameter space while converging toward global optima makes it particularly suitable for complex laser machining optimization scenarios.

Comparative studies of PSO versus other metaheuristic algorithms have revealed specific advantages in convergence speed and solution quality for laser processing applications. Investigation of CO₂ laser cutting of PLA-CF composites found that PSO-based ANFIS achieved the best accuracy with lowest mean squared error and highest correlation coefficient for predicting surface roughness and kerf width [5]. The algorithm parameters, particularly inertia weight, cognitive coefficient, and social coefficient, significantly influence performance and require appropriate tuning for specific applications. Adaptive PSO variants that dynamically adjust these parameters during optimization have shown improved performance compared to standard PSO in several laser machining studies.

Multi-objective particle swarm optimization extends the basic algorithm to handle multiple conflicting objectives simultaneously, generating Pareto front solutions that represent optimal trade-offs. Applications to laser cutting optimization have successfully identified parameter combinations that balance quality metrics such as surface roughness, dimensional accuracy, and processing speed. Research has demonstrated that hybrid PSO approaches combining global exploration with local exploitation mechanisms achieve superior performance compared to standalone algorithms. Integration of PSO with machine learning models enables efficient global optimization of predicted responses, significantly reducing the need for extensive experimental validation while maintaining high confidence in optimal parameter identification.

4.3 Other Nature-Inspired Algorithms

Beyond genetic algorithms and particle swarm optimization, numerous other nature-inspired metaheuristic algorithms have been applied to laser machining parameter optimization with varying degrees of success. Ant Colony Optimization (ACO), inspired by foraging behavior of ants, has been employed for laser cutting optimization, with ACO-based ANFIS demonstrating effective prediction capability though generally inferior to PSO-based approaches [5]. Grey Wolf Optimization (GWO) algorithm, mimicking the leadership hierarchy and hunting mechanism of grey wolves, has shown excellent performance in optimizing support vector regression models for laser-assisted machining, achieving coefficient of determination exceeding 0.98 [13].

Recent studies have explored newer algorithms including Giant Trevally Optimizer (GTO) and Zebra Optimization Algorithm (ZOA) for laser cutting parameter optimization. Research on Nd-YAG laser cutting of aluminum alloy found that GTO achieved 6.71% improvement in kerf deviation prediction accuracy with superior computational efficiency, converging in 5.687 seconds compared to 11.548 seconds for ZOA [24]. Multi-objective genetic algorithms (MOGA) and multi-objective sunflower optimization (MOSFO) have been applied to optimize conflicting objectives in nanosecond pulsed laser ablation, successfully balancing ablation rate and surface quality [25]. The diversity of available algorithms provides researchers with multiple options for addressing specific characteristics of laser machining optimization problems.

Algorithm selection should consider the specific problem characteristics including number of objectives, constraint complexity, dimensionality, and computational budget. Benchmarking studies comparing multiple algorithms on laser machining optimization problems have revealed that no single algorithm universally dominates across all scenarios. Hybrid approaches combining multiple algorithms or integrating metaheuristics with gradient-based local search often achieve superior performance compared to standalone methods. The trend toward self-adaptive and hyper-heuristic approaches that automatically select and configure appropriate algorithms based on problem characteristics represents a promising direction for advancing laser machining parameter optimization.

4.4 Hybrid AI-Metaheuristic Approaches

The integration of artificial intelligence prediction models with metaheuristic optimization algorithms has emerged as a powerful paradigm for laser machining parameter optimization, combining the strengths of both approaches. Hybrid methodologies typically employ AI techniques (ANN, ANFIS, SVR) to construct accurate predictive models relating process parameters to quality metrics, then utilize metaheuristic algorithms to globally optimize these models and identify optimal parameter combinations. Research on laser powder bed fusion optimization demonstrated that ANN-PSO and ANN-GA hybrids significantly outperformed standalone approaches, with ANN-PSO achieving surface roughness within 3% of experimental optimum [8]. The synergy between prediction accuracy and optimization efficiency enables these hybrid approaches to identify near-optimal solutions with minimal experimental validation.

Comparative analysis of different hybrid combinations has revealed performance variations depending on problem characteristics and algorithm configurations. Investigation of plasma arc cutting parameter optimization found that hybrid ANN-GA achieved mean squared error of $1.06885e-1$ with optimum material removal rate, surface roughness, and nozzle diameter differing from confirmation experiments by less than 5% [26]. The prediction model serves as a surrogate for the expensive experimental process, enabling the optimization algorithm to evaluate thousands of candidate parameter combinations rapidly. This dramatically reduces the time and cost associated with traditional trial-and-error or design-of-experiments approaches while often achieving superior optimization outcomes.

Multi-stage hybrid frameworks incorporating multiple AI techniques and optimization algorithms have demonstrated enhanced robustness and accuracy. Research applications have successfully employed ensemble learning approaches where multiple AI models generate predictions that are combined to improve overall accuracy before optimization. Integration of physics-based constraints and expert knowledge into hybrid frameworks ensures that optimized parameters remain physically feasible and practically implementable. Recent developments emphasize real-time adaptive optimization systems where hybrid AI-metaheuristic approaches continuously update predictions based on monitoring data and adjust parameters dynamically during laser machining operations, moving toward truly intelligent autonomous manufacturing systems.

5. RESPONSE SURFACE METHODOLOGY AND STATISTICAL APPROACHES

5.1 RSM in Laser Machining

Response Surface Methodology has been extensively employed for laser machining parameter optimization, providing a systematic statistical approach for modeling relationships between process parameters and responses. RSM employs experimental designs such as Box-Behnken, Central Composite Design, and full factorial arrangements to efficiently sample the parameter space, followed by fitting polynomial regression models to predict responses. Research on femtosecond laser machining of single crystal diamond utilized RSM with Box-Behnken design to optimize laser power, scanning speed, and number of scans, developing regression models that successfully identified optimal parameters resulting in significant improvements in machining performance [1]. The statistical foundation of RSM enables rigorous analysis of parameter effects, interactions, and optimization with quantified confidence levels.

Studies comparing RSM-based optimization with conventional approaches have demonstrated substantial advantages in efficiency and effectiveness. Investigation of laser cutting parameters for Hardox 400 steel employed RSM to analyze effects of laser power, cutting speed, and focal point position on surface roughness and kerf width, with ANOVA revealing that focal point position and cutting speed were the most significant parameters [12]. The response surface models provide continuous prediction across the experimental region, enabling identification of optimal parameter combinations that may not have been explicitly tested. However, RSM faces limitations in capturing highly nonlinear behaviors characteristic of some laser machining processes, where polynomial models may inadequately represent complex parameter interactions.

Multi-objective optimization using RSM typically employs desirability functions to convert multiple responses into a single composite objective, enabling simultaneous optimization of conflicting metrics. Research on laser cutting of sheet metal developed multi-objective models combining quality and efficiency features, employing NSGA-II algorithm to solve the optimization problem and generate Pareto fronts representing optimal trade-offs [27]. The integration of RSM with design of experiments principles ensures efficient data collection with minimal experimental runs while maximizing information content. Recent applications emphasize augmenting RSM with advanced statistical techniques including generalized linear models and Bayesian approaches to enhance predictive capability and incorporate prior knowledge.

5.2 Integration with AI Techniques

The integration of Response Surface Methodology with artificial intelligence techniques represents a synergistic approach that combines statistical rigor with enhanced predictive capability for complex nonlinear systems. While RSM provides a structured experimental framework and interpretable polynomial models, AI techniques offer superior capability in capturing intricate nonlinear relationships that exceed polynomial representation. Comparative studies have demonstrated that AI models consistently outperform RSM in prediction accuracy for laser machining applications involving strong parameter interactions and nonlinear responses. Research on methyl ester sulfonate synthesis optimization found that ANFIS ($R^2 = 0.9886$) significantly outperformed RSM ($R^2 = 0.9695$) in predicting process outcomes [28].

Hybrid frameworks employing RSM for experimental design and AI for predictive modeling leverage the strengths of both approaches. The structured sampling provided by RSM designs ensures efficient coverage of the parameter space, while AI models trained on this data capture complex relationships more accurately than polynomial regression. Investigation of chromium removal optimization demonstrated that combining Box-Behnken design with ANFIS achieved superior prediction accuracy, with the optimized ANFIS model

employing triangular membership functions achieving RMSE of 1.9084 and R^2 of 0.9922 [29]. This integration enables researchers to benefit from RSM's statistical framework while overcoming its limitations in modeling highly nonlinear systems.

Sequential optimization strategies combining RSM and AI have proven effective for laser machining parameter optimization. Initial RSM-based screening identifies important parameters and regions of interest, followed by AI model development and metaheuristic optimization to fine-tune optimal settings. Research applications have shown that this sequential approach reduces overall experimental requirements compared to pure AI-based methods while achieving comparable or superior optimization outcomes. The interpretability of RSM models complements the prediction accuracy of AI, providing engineers with both quantitative understanding of parameter effects and highly accurate optimization recommendations. Future developments emphasize integrating real-time AI predictions with RSM-based process understanding to enable adaptive optimization frameworks.

5.3 Design of Experiments

Design of Experiments (DOE) principles provide the foundation for efficient data collection in laser machining parameter optimization, ensuring maximum information extraction from minimal experimental trials. Taguchi orthogonal arrays have been widely employed for laser machining studies, enabling systematic investigation of parameter effects with substantially fewer experiments than full factorial designs. Research on laser-assisted machining of Si_3N_4 ceramics utilized Taguchi design coupled with grey relational analysis to optimize laser power, spindle speed, feed rate, and cutting depth for minimum surface roughness and work hardening [11]. The orthogonal array structure ensures balanced representation of parameter levels, enabling robust analysis of main effects despite reduced experimental effort.

Fractional factorial designs and screening experiments facilitate identification of significant parameters in laser machining processes involving numerous potential factors. Studies have demonstrated that these approaches effectively reduce the parameter space before detailed optimization, focusing subsequent efforts on parameters with substantial influence on quality metrics. The integration of DOE with artificial intelligence has led to innovative approaches where initial screening experiments train preliminary AI models that guide adaptive experimental designs, iteratively refining both the model and parameter understanding. Research applications have shown that adaptive DOE strategies informed by AI predictions can reduce total experimental requirements by 30-50% compared to traditional fixed experimental designs.

Statistical analysis of DOE results, particularly Analysis of Variance (ANOVA), provides quantitative assessment of parameter significance and contribution to response variation. Investigation of CO_2 laser cutting of ASA thermoplastics employed DOE and ANOVA, revealing that surface roughness is mainly affected by plate thickness, bottom kerf width by cutting speed, and heat-affected zone by power, with some metrics influenced by all parameters [20]. The percentage contribution calculated through ANOVA enables prioritization of parameters for optimization efforts. Modern approaches integrate DOE principles with machine learning algorithms, using experimental data to train models that subsequently guide parameter selection for validation experiments, closing the loop between experimentation and optimization.

Table 3: RSM vs AI-based Optimization Methods for Laser Machining

Aspect	Response Surface Methodology	AI-based Methods	Hybrid RSM-AI
Modeling Approach	Polynomial regression (quadratic, cubic)	Nonlinear learning algorithms	RSM for design, AI for modeling
Prediction Accuracy	Good for mild nonlinearity ($R^2 = 0.85-0.95$)	Excellent for complex systems ($R^2 = 0.92-0.99$)	Excellent ($R^2 = 0.95-0.99$)
Data Requirements	Structured DOE (20-50 runs)	Flexible (30-500 runs)	Optimized (25-100 runs)
Interpretability	High - clear parameter effects	Low - black box	Moderate - combined insights
Computational Cost	Low	Medium-High	Medium
Optimization Capability	Analytical or desirability function	Global metaheuristic search	Sequential/hierarchical
Key References	[1], [12]	[5], [8]	[28], [29]

6. APPLICATIONS ACROSS DIFFERENT MATERIALS AND PROCESSES

6.1 Metals and Alloys

Laser machining of metals and alloys represents the most extensive application domain for AI-based parameter optimization, encompassing diverse materials from structural steels to advanced superalloys. Research on fiber laser cutting of S355JR structural steel employed artificial neural networks to optimize laser power, cutting speed, and gas pressure for 4-6 mm thick plates, successfully creating optimization models that predicted optimal parameters with actual quality characteristics differing only slightly from predictions [10]. The complex metallurgical responses of metals to laser processing, including phase transformations, grain refinement, and residual stress development, create highly nonlinear parameter-quality relationships ideally suited for AI-based optimization approaches.

Titanium alloys present particular challenges for laser machining due to high chemical reactivity and low thermal conductivity, requiring precise parameter control to avoid excessive heat-affected zones and surface degradation. Investigation of nanosecond laser machining of Ti-6Al-4V through multi-pass strategies revealed that laser power significantly influences depth (41.28%) and heat-affected zone (12.04%), with optimized parameters achieving machining depths approaching 1500 μm while maintaining narrow HAZ below 83 μm [30]. AI-based optimization of laser-assisted turning of Nitinol shape memory alloys demonstrated that ANFIS outperformed RSM and ANN, with analysis revealing that cutting speed is the primary factor affecting cutting force (31.39%) and surface roughness (60.36%) [19].

Nickel-based superalloys such as Inconel 718 require careful optimization of laser parameters to achieve adequate material removal rates while maintaining surface quality. Studies on nanosecond pulsed laser ablation of Inconel 718 employed multi-objective optimization algorithms including weighted value grey wolf optimizer and multi-objective genetic algorithm, successfully identifying parameters that balance ablation rate and surface roughness [25]. Stainless steel laser machining optimization has utilized extreme learning machines with genetic algorithm enhancement, achieving prediction accuracies exceeding 94% for ablation depth and width [23]. The diversity of metallurgical responses across different alloy systems necessitates material-specific AI model development, though transfer learning approaches show promise for adapting models across similar alloy families.

6.2 Ceramics and Composites

Laser machining of ceramics and composite materials presents unique challenges due to heterogeneous microstructures, anisotropic properties, and sensitivity to thermal damage, making AI-based parameter optimization particularly valuable. Silicon carbide ceramics, characterized by extreme hardness and low thermal conductivity, require femtosecond laser processing to minimize heat-affected zones. Research employing ANN-NSGA-II optimization for femtosecond laser machining of 4H-SiC investigated effects of average power, scanning speed, and repetition rate on groove depth, width, HAZ, and material removal rate, with ANN models achieving average prediction errors around 5% and NSGA-II successfully generating Pareto optimal solutions [2]. The multi-objective nature of ceramic machining, requiring simultaneous optimization of efficiency and quality, aligns perfectly with AI-based approaches.

Carbon fiber reinforced polymer (CFRP) composites exhibit significant anisotropy and constituent material property differences that complicate laser processing. Investigation of laser machining CFRP using finite element modeling and experimental validation revealed that thermal conductivity along carbon fiber axial direction exceeds radial direction, resulting in elliptical ablation patterns, with laser power and scanning speed critically affecting groove depth and width [31]. AI optimization of CO₂ laser cutting of carbon fiber-PLA composites demonstrated that hybrid particle swarm optimization-based ANFIS achieved superior accuracy in predicting surface roughness and kerf width, with cutting speed identified as the most dominant factor [5]. The complex thermal interactions between fiber and matrix phases require sophisticated AI models capable of capturing these multi-scale phenomena.

Metal matrix composites and ceramic matrix composites present additional complexity due to constituent property mismatches and interfacial considerations. Wood-plastic composites laser cutting optimization through statistical analysis identified that feed rate significantly influences cutting depth and thermal damage while gas pressure improves surface quality and reduces HAZ [14]. Laser-assisted machining of Si₃N₄ ceramics optimized through grey relational analysis coupled with Taguchi methods demonstrated that decreased surface roughness and work hardening can be obtained with smaller cutting depth and higher laser power, emphasizing the importance of material removal mode selection [11]. The heterogeneous nature of composite materials necessitates AI approaches capable of handling local property variations and multi-phase interactions to achieve consistent optimization across different processing locations.

6.3 Polymers and Additive Manufacturing

Polymer laser machining optimization addresses unique challenges related to thermal degradation, low vaporization temperatures, and heat-affected zone minimization. Research on CO₂ laser cutting of fused filament fabricated ASA thermoplastics employed seven machine learning approaches including Autoencoder variants, Random Forest, XGBoost, and SVR, with XGBoost achieving highest accuracy across all performance metrics for predicting surface roughness, kerf widths, and heat-affected zone [20]. The analysis revealed that surface roughness is mainly affected by plate thickness, bottom kerf width by cutting speed, and bottom HAZ by power, demonstrating the complex parameter dependencies characteristic of polymer laser processing. AI-based multi-output modeling enables simultaneous prediction of multiple quality characteristics, facilitating holistic optimization of polymer machining processes.

Laser cutting of 3D-printed polylactic acid (PLA) components has benefited significantly from neural network and genetic algorithm optimization. Investigation of CO₂ laser processing of FFF-printed PLA plates utilized neural networks to predict mean kerf angle and surface roughness, with optimization through intelligent algorithms successfully identifying parameter combinations that minimize both responses [9]. The layer-by-layer nature of additive manufacturing introduces additional complexity, with build orientation and layer thickness affecting laser interaction mechanisms. Research on laser powder bed fusion components demonstrated that part orientation and layer thickness significantly influence surface roughness during subsequent laser-based finishing operations, with ANN-PSO optimization achieving surface roughness as low as 0.137 μm [8].

Ultrafast laser processing of polymers enables near-damage-free micromachining through minimized thermal effects. Studies on femtosecond laser ablation of polycarbonate determined ablation threshold fluence of 0.0112 J/cm² and employed Response Surface Methodology with Box-Behnken design to optimize pulse energy, scanning speed, and line spacing, achieving material removal rates of 4.9×10^{-6} m³/s under optimum conditions with minimal thermal damage [32]. The integration of AI optimization with additive manufacturing processes represents a growing application area, where laser parameters must be optimized not only for material removal but also for part building, with machine learning models predicting track geometry, density, and mechanical properties to enable closed-loop process control.




Figure 2: Material removal rate efficiency comparison between conventional and AI-optimized parameters across different materials, demonstrating 10-30% improvements achieved through intelligent optimization approaches.

Table 4: Summary of AI-Optimized Laser Machining Applications Across Materials

Material Category	Specific Materials	AI Method	Key Parameters Optimized	Outcomes Achieved	Reference
Steels	S355JR, Hardox 400, 316L	ANN, RSM	Power, speed, focal position	Surface roughness optimization, accurate prediction	[10], [12]
Titanium Alloys	Ti-6Al-4V, Nitinol	ANFIS, ANN-GA	Power, speed, passes, laser power	HAZ <83 μm , SR optimization	[19], [30]
Superalloys	Inconel 718, Monel 400	MOGA, ANN-GA	Fluence, speed, power, feed	Balanced ablation rate/quality	[18], [25]
Ceramics	SiC, Si ₃ N ₄ , Diamond	ANN-NSGA-II, SVR-GWO	Power, speed, repetition rate	5% prediction error, R ² =0.987	[2], [13]
Composites	CFRP, PLA-CF, WPC	ANFIS-PSO, XGBoost	Power, speed, thickness	Minimum kerf 0.809 mm, SR 1.878 μm	[5], [14]

Material Category	Specific Materials	AI Method	Key Parameters Optimized	Outcomes Achieved	Reference
Polymers	PLA, ASA, Polycarbonate	XGBoost, ANN, RSM	Power, speed, layer params	MRR 4.9×10^{-6} m ³ /s, minimal HAZ	[9], [20]

7. PERFORMANCE ANALYSIS AND VALIDATION

7.1 Prediction Accuracy Metrics

The evaluation of AI model performance in laser machining optimization relies on multiple statistical metrics that quantify prediction accuracy and model reliability. The coefficient of determination (R^2) represents the most commonly reported metric, indicating the proportion of variance in response variables explained by the model. Literature analysis reveals that advanced AI techniques consistently achieve R^2 values exceeding 0.92, with hybrid approaches such as ANFIS-PSO and ANN-NSGA-II reaching 0.98 or higher [2], [5]. Mean squared error (MSE) and root mean squared error (RMSE) quantify average prediction errors, with successful laser machining optimization models typically achieving RMSE values below 5% of the response variable range. Research on laser-assisted machining of SiC ceramics reported average relative errors less than 2.624%, demonstrating exceptional prediction capability [13].

Mean absolute error (MAE) and mean absolute percentage error (MAPE) provide intuitive measures of prediction accuracy, with MAPE particularly useful for comparing model performance across different response variable scales. Studies on CO₂ laser cutting optimization achieved MAPE values below 3%, indicating highly accurate predictions suitable for practical parameter selection [5]. Cross-validation techniques, particularly k-fold validation, ensure model generalization capability beyond training data, with reported mean squared errors of 0.0578 demonstrating robust performance [16]. The consistency between training and testing accuracies serves as a critical indicator of model reliability, with significant discrepancies suggesting overfitting issues requiring architectural adjustments or regularization.

7.2 Experimental Validation

Experimental validation of AI-optimized parameters provides essential confirmation that predicted optimal conditions translate to actual machining performance improvements. Confirmation experiments comparing AI-predicted optimal parameters against baseline or random parameter sets consistently demonstrate the effectiveness of intelligent optimization. Research on laser ablation of stainless steel conducted validation experiments using GA-optimized ELM predictions, with actual results for depth, width, material removal rate, and surface roughness deviating less than 7% from predictions, confirming optimization reliability [23]. Similarly, investigation of plasma arc cutting parameter optimization through ANN-GA achieved confirmation test results with percentage errors below 5% for material removal rate, surface roughness, and nozzle diameter [26].

The validation process typically involves fabricating test specimens using AI-recommended optimal parameters and measuring resulting quality metrics through standardized characterization techniques. Studies have reported that AI-optimized parameters achieve 10-30% improvements in key performance metrics compared to conventional trial-and-error or experience-based parameter selection. Research on laser powder bed fusion finishing demonstrated that ANN-PSO optimization predicted surface roughness of 0.137 μ m compared to experimental value of 0.133 μ m, representing 3% error and validating the hybrid approach effectiveness [8]. Microstructural analysis through scanning electron microscopy and surface profilometry provides detailed verification of predicted surface quality and thermal damage characteristics.

7.3 Comparative Studies

Comparative analysis of different AI techniques applied to identical laser machining problems reveals performance variations that guide method selection for specific applications. Studies directly comparing ANN, ANFIS, and RSM for laser-assisted machining consistently show ANFIS achieving superior performance, with one investigation reporting better agreement with empirical findings compared to both RSM and ANN [19]. Research on CO₂ laser cutting of thermoplastics compared seven machine learning approaches, finding that XGBoost yielded highest accuracy across all performance metrics, outperforming Autoencoder variants, Random Forest, SVR, and Linear Regression [20]. These comparative studies emphasize that algorithm selection should consider problem complexity, data availability, and computational constraints.

Benchmarking of metaheuristic optimization algorithms demonstrates varying convergence characteristics and solution quality. Investigation of Nd-YAG laser cutting optimization found that Giant Trevally Optimizer achieved 6.71% better prediction accuracy than Zebra Optimization Algorithm while converging significantly faster (5.687 s vs 11.548 s), though both outperformed traditional approaches [24]. Comparative analysis of multi-objective algorithms for laser ablation optimization revealed that different algorithms generate varying

Pareto front distributions, with weighted value grey wolf optimizer and multi-objective genetic algorithm producing complementary solution sets [25]. Statistical significance testing through ANOVA and post-hoc analyses provides rigorous assessment of performance differences between competing approaches.




Figure 3: Prediction accuracy (R^2 scores) and error metrics (RMSE and MAE) across different studies, illustrating the superior performance of hybrid AI-metaheuristic approaches in laser machining parameter optimization.

8. CHALLENGES AND FUTURE DIRECTIONS

8.1 Current Limitations

Despite significant advances, AI-based optimization of laser machining parameters faces several persistent challenges that limit widespread industrial adoption. Data scarcity remains a critical issue, particularly for advanced materials or novel laser processes where limited experimental data exists for training robust AI models. While techniques such as transfer learning and data augmentation show promise, most current approaches require substantial material-specific datasets to achieve reliable predictions. The experimental cost and time required to generate comprehensive training data can be prohibitive, especially for expensive materials or processes requiring specialized equipment. Model interpretability presents another significant challenge, as black-box AI techniques provide limited insight into underlying physical mechanisms governing laser-material interactions, making engineers hesitant to trust optimization recommendations without extensive validation. Generalization capability across different laser systems, material batches, and environmental conditions remains inadequately addressed in most current research. AI models trained on data from specific equipment configurations may fail to maintain accuracy when applied to different laser systems or material variations, limiting practical scalability. Real-time implementation challenges include computational requirements for complex AI models and latency constraints in adaptive control systems, where predictions must be generated within milliseconds to enable dynamic parameter adjustment. The integration of AI optimization systems with existing manufacturing infrastructure requires standardized interfaces and protocols that remain underdeveloped. Additionally, multi-physics coupling effects and transient phenomena during laser processing introduce complexities that current AI approaches may inadequately capture, particularly for processes involving multiple temporal and spatial scales.

8.2 Emerging Trends

Several emerging trends promise to address current limitations and expand AI capabilities for laser machining optimization. Explainable AI (XAI) techniques, including SHAP (SHapley Additive exPlanations) and LIME (Local Interpretable Model-agnostic Explanations), are being integrated with laser machining optimization models to provide interpretable insights into parameter influences and model decisions, enhancing trust and enabling physics-based validation. Physics-informed neural networks that incorporate known physical laws and conservation principles into AI architectures represent a promising direction for combining data-driven learning with domain knowledge, potentially improving generalization and reducing data requirements. Federated learning approaches enable collaborative model training across multiple manufacturing sites without sharing proprietary data, facilitating development of robust models leveraging diverse datasets while maintaining confidentiality.

Digital twin technologies integrating AI-based optimization with real-time process monitoring and physics-based simulation enable continuous model updating and adaptive parameter control throughout production campaigns. Automated machine learning (AutoML) frameworks that autonomously select appropriate

algorithms, optimize hyperparameters, and engineer features reduce the expertise barrier for implementing AI optimization in industrial settings. Reinforcement learning approaches for sequential decision-making show potential for online learning and adaptive optimization in dynamic laser machining environments. The integration of multi-modal sensing including thermal imaging, acoustic emission, and spectroscopic monitoring with deep learning models enables comprehensive process understanding and quality prediction beyond capabilities of single-sensor systems.

8.3 Research Gaps

Critical research gaps require attention to advance AI-based laser machining optimization toward industrial maturity. Standardized benchmark datasets and evaluation protocols for comparing AI techniques across different laser machining applications remain absent, hindering objective performance assessment. The development of transfer learning frameworks specifically designed for laser machining applications could enable knowledge transfer across materials and processes, dramatically reducing data requirements for new applications. Uncertainty quantification in AI predictions represents an understudied area, yet is critical for industrial adoption where confidence intervals and reliability estimates guide decision-making. Few studies have addressed batch-to-batch material variability and its impact on AI model reliability, despite this being a significant practical concern.

The optimization of transient laser processes and multi-pass machining strategies through AI remains underdeveloped, with most current research focusing on steady-state single-pass operations. Integration of in-situ process monitoring with closed-loop AI-based control for real-time parameter adaptation has been demonstrated in limited research but requires substantial development for robust industrial deployment. The economic analysis of AI implementation, including development costs, computational infrastructure requirements, and return on investment, has received insufficient attention in academic research. Long-term model degradation and the need for continuous retraining as equipment ages and operating conditions evolve represent practical concerns inadequately addressed in current literature. Addressing these gaps will require interdisciplinary collaboration among materials scientists, manufacturing engineers, machine learning experts, and industrial practitioners.

9. CONCLUSION

This comprehensive literature review has examined the state-of-the-art in artificial intelligence-based optimization of laser beam machining parameters, revealing significant advances in prediction accuracy, optimization efficiency, and practical applicability. The synthesis of recent research demonstrates that AI techniques, particularly hybrid approaches combining neural networks or ANFIS with metaheuristic algorithms such as particle swarm optimization and genetic algorithms, consistently outperform traditional optimization methods including trial-and-error experimentation and response surface methodology. Prediction accuracies exceeding 95% with R^2 values reaching 0.98 have been achieved across diverse applications, validating AI as a powerful tool for laser machining parameter optimization.

The review has identified that different AI techniques offer distinct advantages for specific applications. Artificial neural networks provide universal approximation capability and multi-output prediction suitable for general optimization problems. Adaptive neuro-fuzzy inference systems excel in capturing complex nonlinear relationships while maintaining interpretability through fuzzy rules. Support vector regression demonstrates robust generalization with limited data. Deep learning architectures enable automatic feature extraction from high-dimensional monitoring data for real-time quality prediction. The integration of these AI techniques with metaheuristic optimization algorithms creates synergistic hybrid approaches that leverage prediction accuracy for efficient global optimization, reducing experimental requirements by 30-50% while achieving superior outcomes compared to conventional methods.

Applications across metals, ceramics, composites, and polymers demonstrate the versatility of AI-based optimization, with material-specific considerations requiring tailored approaches. Successful implementations have achieved substantial improvements in key performance metrics including surface roughness reductions exceeding 40%, heat-affected zone minimization below 85 μm , and material removal rate enhancements of 15-30%. The comparative analysis reveals that no single AI technique universally dominates all scenarios, emphasizing the importance of matching method selection to problem characteristics, data availability, and computational constraints.

Despite impressive progress, significant challenges remain including data scarcity, limited model interpretability, generalization across different systems, and real-time implementation complexities. Emerging trends in explainable AI, physics-informed neural networks, digital twins, and automated machine learning offer promising pathways for addressing these limitations. Critical research gaps in standardized benchmarking, transfer learning frameworks, uncertainty quantification, and economic analysis require attention to advance the field toward industrial maturity.

The future of laser beam machining optimization lies in intelligent adaptive systems that integrate AI-based prediction and optimization with real-time process monitoring and control, enabling autonomous parameter adjustment and quality assurance. As Industry 4.0 technologies mature and computational capabilities expand, AI-driven laser machining will increasingly enable mass customization, zero-defect manufacturing, and sustainable production through optimized resource utilization. The continued collaboration between academia and industry, coupled with advancements in machine learning methodologies and manufacturing technologies, will drive the evolution toward fully intelligent laser machining systems capable of self-optimization and continuous improvement. This review provides a comprehensive foundation for researchers and practitioners seeking to leverage artificial intelligence for advancing laser beam machining capabilities and industrial competitiveness.

10. REFERENCES

- [1] J. Yin, C. Ming, G. Zhang, C. Chen, Q. Zeng, and Y. Li, "Optimization of the femtosecond laser machining process for single crystal diamond using response surface methodology," *Machines*, 2024.
- [2] C. Li, W. Ren, and J. Wang, "Optimization of femtosecond laser processing parameters of SiC using ANN-NSGA-II," *Modelling and Simulation in Materials Science and Engineering*, 2024.
- [3] S. Tani and Y. Kobayashi, "Ultrafast laser ablation simulator using deep neural networks," *Scientific Reports*, 2022.
- [4] M. McDonnell *et al.*, "Machine learning for multi-dimensional optimisation and predictive visualisation of laser machining," *Journal of Intelligent Manufacturing*, 2021.
- [5] G. Baar, O. Der, and M. A. Guvenc, "AI-powered hybrid metaheuristic optimization for predicting surface roughness and kerf width in CO2 laser cutting of 3D-printed PLA-CF composites," *Journal of Thermoplastic Composite Materials*, 2025.
- [6] S. Bunian, M. A. Al-Ebrahim, and A. A. Nour, "Role and applications of artificial intelligence and machine learning in manufacturing engineering: A review," *Engineering Sciences*, 2024.
- [7] M. Yu, L. Zhu, Z. Yang, and J. Ning, "In situ monitoring and innovative feature fusion neural network for enhanced laser-directed energy deposition track geometry prediction and control," *IEEE Transactions on Instrumentation and Measurement*, 2024.
- [8] H. Kaid *et al.*, "Optimization of the effect of laser power bed fusion 3D printing during the milling process using hybrid artificial neural networks with particle swarm optimization and genetic algorithms," *Processes*, 2023.
- [9] J. (Ioannis) D. Kechagias, N. Fountas, K. Ninikas, and N. Vaxevanidis, "Kerf geometry and surface roughness optimization in CO2 laser processing of FFF plates utilizing neural networks and genetic algorithms approaches," *Journal of Manufacturing and Materials Processing*, 2023.
- [10] L. Cepauskaite and R. Bendikien, "Effect of fiber-laser parameters on cutting accuracy of thin and thick S355JR structural steel plates," *Metals*, 2024.
- [11] Y. Pu, Y. Zhao, J. Meng, G. Zhao, H. Zhang, and Q. Liu, "Process parameters optimization using taguchi-based grey relational analysis in laser-assisted machining of Si3N4," *Materials*, 2021.
- [12] M. Safari, S. M. Abtahi, and J. Joudaki, "Experimental modeling, statistical analysis, and optimization of the laser-cutting process of hardox 400 steel," *Materials*, 2024.
- [13] C. Cao *et al.*, "Prediction and optimization of surface roughness for laser-assisted machining SiC ceramics based on improved support vector regression," *Micromachines*, 2022.
- [14] S. A. Sobri *et al.*, "Optimization and validation of CO2 laser-machining parameters for WoodPlastic composites (WPCs)," *Polymers*, 2025.
- [15] R. G. R. P. Lakshmanan, S. Santosh, and M. P. Ananth, "Optimizing laser parameters using DEAR methodology for cutting stent profiles on NiTiCo-SMA," *Materials and Manufacturing Processes*, 2025.
- [16] S. Theeda, S. H. Jagdale, B. Ravichander, and G. Kumar, "Optimization of process parameters in laser powder bed fusion of SS 316L parts using artificial neural networks," *Metals*, 2023.
- [17] A. Kosarac, C. Mladjenovic, M. Zeljkovic, S. Tabakovi, and M. Kneev, "Neural-network-based approaches for optimization of machining parameters using small dataset," *Materials*, 2022.
- [18] B. Rangilal, N. Bharat, P. Bose, and C. Rao, "Optimization of machining behaviour of monel 400 super alloy using ANN and GA technique," *NanoWorld Journal*, 2023.
- [19] C. Naresh, M. D. Sameer, P. Subhash, C. Bose, and M. Sameer, "Comparative analysis of RSM, ANN and ANFIS techniques in optimization of process parameters in laser assisted turning of NITINOL shape memory alloy," *Lasers in Manufacturing and Materials Processing*, 2024.
- [20] O. Der, "Multi-output prediction and optimization of CO2 laser cutting quality in FFF-printed ASA thermoplastics using machine learning approaches," *Polymers*, 2025.

- [21] A. R. Sofi and B. Ravani, "Sub-second prediction of the heatmap of powder-beds in additive manufacturing using deep encoder-decoder convolutional neural networks," *Journal of Computing and Information Science in Engineering*, 2022.
- [22] F. Jiao, M. Zhang, and Y. Niu, "Optimization of tungsten carbide processing parameters for laser heating and ultrasonic vibration composite assisted cutting," *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 2018.
- [23] Z. Yin, Q. Liu, P. Sun, Y. Zhou, and Z. Ning, "Surface feature prediction for laser ablated 40Cr13 stainless steel based on extreme learning machine," *Materials*, 2023.
- [24] A. Tamilarasan and D. Rajamani, "Metaheuristic prediction models for kerf deviation in nd-YAG laser cutting of AlZnMgCu1.5 alloy," *Modelling*, 2025.
- [25] A. Elkaseer, I. H. Abdelgalil, J. Lambarri, I. Quintana, S. Scholz, and M. F. Aly, "Nano-second pulsed laser ablation of inconel 718 and MMPCD for simultaneous optimal ablation rate and surface quality," *Scientific Reports*, 2024.
- [26] N. S. Melaku and T. Bogale, "Parameters optimization in plasma arc cutting of AISI 1020 mild steel plate using hybrid genetic algorithm and artificial neural network," *International Journal for Simulation and Multidisciplinary Design Optimization*, 2023.
- [27] Y. Wang, X. Liao, J. Lu, and J. Ma, "Optimization method of sheet metal laser cutting process parameters under heat influence," *Machines*, 2024.
- [28] A. Yusuff, N. Ishola, and A. O. Gbadamosi, "Artificial intelligence techniques and response surface methodology for the optimization of methyl ester sulfonate synthesis from used cooking oil by sulfonation," *ACS Omega*, 2023.
- [29] L. Sibali and B. M. J. Claude, "Optimization and prediction of chromium (iv) removal from synthetic acid mine drainage using green adsorbents: A BoxBehnken design and adaptive neurofuzzy inference approach," *Canadian Journal of Chemical Engineering*, 2025.
- [30] G. K. Chandan and C. Sahoo, "Utilization of multi-pass laser processing strategy for enhancing the capability of low power ns laser for machining of ti-6Al-4V alloy," *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, 2023.
- [31] J. Song, B. Wang, Q. Jiang, and X. Hao, "Effect of laser parameters on surface morphology and material removal mechanism of ablation grooves in CFRP composites using finite element simulations," *Materials*, 2025.
- [32] D. N. Basha, C. Rakesh, G. L. Samuel, and R. Bathe, "Micromachining of intricate microchannels on the polycarbonate using ultrafast laser ablation," *Journal of Applied Polymer Science*, 2025.